



INDUSTRY 4.0

Machine with built-in OPC-UA interface

Highlights & Performance

- Servo motor + Electric roller linear cylinder drive
- Piston pump metering system
- Visual HMI operation interface
- 12-inch Touch Screen
- Advance precision, automatic proportional adjustment according to settings
- Closed loop monitoring with built-in or as options
- Quiet, low energy consumption, oil free operation
- Cleanroom suitability and high-end product production
- Can be customized for special applications.

Available Options

- Ready for additional expansion
- High precision color line available
- Optimization upon request

LSR e-Master



OPTIONS



TECHNICAL DATA

Viscosity	1,000,000 mPas
Output mixed material	800 g/min (depending on viscosity)
Mixing ratio	1:1 or variable
Color metering	0.3% ~ 4%
Actuation	Servo motor drive
Electric data	230-400 VAC, 50-60 Hz (3P+PE), 16A
Connection LIM machine	24V
Pneumatic system	R1/4", 6 bar low
Weight	745 kg
Dimensions	1,046 x 1,200 x 1,950 mm (W x D x H) (Height +600 mm if pump completely lifted)



2KM MUCOMAC Multi component special machinery (Guangzhou) Co., Ltd.
Add: No. Sheng Li Industrial Park North of Chao tian industrial zone shi Lian Lu
Shi Lou Town Panyu Distri Guangzhou P.R.C Postcode: 511447

Tel: +8620 - 34852366 / 2866
Fax: +8620 - 34852966 / 2566
Email: info@2kmmucomac.com

www.2kmmucomac.com

www.mucomac.com

Service hotline
400-900-3889